

What is claimed as new and what is desired to secure by Letters Patent of the United States is:

1. A barbeque grill for outdoor cooking comprising:

5 a base member having a longitudinal axis and a substantially planar bottom surface, said base member further having a plurality of sidewalls integral therewith and extending substantially vertically therefrom, said base member including a plurality of spaced support rails slidably engageable with said bottom surface and for guiding said base member between retracted and extended positions
10 substantially parallel to the axis;

a plurality of elongated support legs connected to said plurality of support rails respectively and extending substantially vertically adjacent to said base member;

a pair of opposed side panels having top and bottom edge portions and
15 being secured to said plurality of support legs, said side panels extending substantially parallel to said plurality of support legs along a vertical plane and defining a cavity therebetween;

a top member having front and rear edge portions positioned along a length of said top edge portions respectively and extending across the cavity, said rear
20 edge portion being pivotally connected to one said side panels so that said top member can be selectively moved between open and closed positions, said top member including a grill surface for supporting foodstuff thereon and being spaced above said cavity;

a plurality of baskets for storing charcoal therein, said plurality of baskets
25 having a generally rectangular shape and extending adjacent a length of said side panels, said baskets being disposed substantially medially between said base member and said top member and extending substantially parallel to the axis;

a drip pan for collecting and directing grease downwardly and away from said plurality of baskets, said drip pan having opposed edge portions and a central
30 portion converging medially and downwardly therefrom;

a reservoir removably positionable on said bottom surface of said base member, said reservoir for receiving grease drippings directed downwardly and away from said drip pan; and

a plurality of access doors pivotally connected to said side panels
5 respectively and extending along a partial length thereof and substantially parallel to the axis, said plurality of access doors being disposed adjacent said plurality of baskets and being movable between open and closed positions so that a user can effectively access the cavity.

10 2. The barbecue grill of claim 1, further comprising: a plurality of wheels pivotally secured to said plurality of support legs respectively and for allowing said barbecue grill to be rolled along a ground surface.

15 3. The barbecue grill of claim 1, wherein said top member further comprises: a lid pivotally connected thereto and for selectively covering said grill surface during cooking operations.

20 4. The barbecue grill of claim 1, wherein said drip pan has rear and front portions offset above and below the axis respectively.

5. The barbecue grill of claim 1, wherein said drip pan is disposed substantially medially of said plurality of baskets and is engaged therewith respectively.

25 6. The barbecue grill of claim 3, wherein said lid comprises: a handle connected thereto and for assisting a user to selectively pivot said lid between open and closed positions.

30 7. The barbecue grill of claim 1, wherein said drip pan has a generally V-shape cross-section.

8. The barbeque grill of claim 1, wherein said reservoir has a substantially cylindrical shape.

5 9. The barbeque grill of claim 1, wherein said plurality of access doors are selectively pivotal within a select quadrant respectively.

10 10. A barbeque grill for outdoor cooking comprising:
a base member having a longitudinal axis and a substantially planar bottom surface, said base member further having a plurality of sidewalls integral therewith and extending substantially vertically therefrom, said base member including a plurality of spaced support rails slidably engageable with said bottom surface and for guiding said base member between retracted and extended positions substantially parallel to the axis;
a plurality of elongated support legs connected to said plurality of support rails respectively and extending substantially vertically adjacent to said base member;
a plurality of wheels pivotally secured to said plurality of support legs respectively and for allowing said barbecue grill to be rolled along a ground surface;
a pair of opposed side panels having top and bottom edge portions and being secured to said plurality of support legs, said side panels extending substantially parallel to said plurality of support legs along a vertical plane and defining a cavity therebetween;
a top member having front and rear edge portions positioned along a length of said top edge portions respectively and extending across the cavity, said rear edge portion being pivotally connected to one said side panels so that said top member can be selectively moved between open and closed positions, said top member including a grill surface for supporting foodstuff thereon and being spaced above said cavity;
a plurality of baskets for storing charcoal therein, said plurality of baskets having a generally rectangular shape and extending adjacent a length of said side

15
20
25
30

panels, said baskets being disposed substantially medially between said base member and said top member and extending substantially parallel to the axis;

a drip pan for collecting and directing grease downwardly and away from said plurality of baskets, said drip pan having opposed edge portions and a central
5 portion converging medially and downwardly therefrom;

a reservoir removably positionable on said bottom surface of said base member, said reservoir for receiving grease drippings directed downwardly and away from said drip pan; and

a plurality of access doors pivotally connected to said side panels
10 respectively and extending along a partial length thereof and substantially parallel to the axis, said plurality of access doors being disposed adjacent said plurality of baskets and being movable between open and closed positions so that a user can effectively access the cavity.

15 11. The barbeque grill of claim 10, wherein said top member further comprises: a lid pivotally connected thereto and for selectively covering said grill surface during cooking operations.

20 12. The barbeque grill of claim 10, wherein said drip pan has rear and front portions offset above and below the axis respectively.

25 13. The barbeque grill of claim 10, wherein said drip pan is disposed substantially medially of said plurality of baskets and is engaged therewith respectively.

14. The barbeque grill of claim 11, wherein said lid comprises: a handle connected thereto and for assisting a user to selectively pivot said lid between open and closed positions.

15. The barbeque grill of claim 10, wherein said drip pan has a generally V-shaped cross-section.

5 16. The barbeque grill of claim 10, wherein said reservoir has a substantially cylindrical shape.

17. The barbeque grill of claim 10, wherein said plurality of access doors are selectively pivotal within a select quadrant respectively.

10 18. A barbeque grill for outdoor cooking comprising:

a base member having a longitudinal axis and a substantially planar bottom surface, said base member further having a plurality of sidewalls integral therewith and extending substantially vertically therefrom, said base member including a plurality of spaced support rails slidably engageable with said bottom surface and
15 for guiding said base member between retracted and extended positions substantially parallel to the axis;

a plurality of elongated support legs connected to said plurality of support rails respectively and extending substantially vertically adjacent to said base member;

20 a plurality of wheels pivotally secured to said plurality of support legs respectively and for allowing said barbecue grill to be rolled along a ground surface;

a pair of opposed side panels having top and bottom edge portions and being secured to said plurality of support legs, said side panels extending substantially parallel to said plurality of support legs along a vertical plane and
25 defining a cavity therebetween;

a top member having front and rear edge portions positioned along a length of said top edge portions respectively and extending across the cavity, said rear edge portion being pivotally connected to one said side panels so that said top member can be selectively moved between open and closed positions, said top

member including a grill surface for supporting foodstuff thereon and being spaced above said cavity;

a plurality of baskets for storing charcoal therein, said plurality of baskets having a generally rectangular shape and extending adjacent a length of said side panels, said baskets being disposed substantially medially between said base member and said top member and extending substantially parallel to the axis;

a drip pan for collecting and directing grease downwardly and away from said plurality of baskets, said drip pan having opposed edge portions and a central portion converging medially and downwardly therefrom, said drip pan having rear and front portions offset above and below the axis respectively.

a reservoir removably positionable on said bottom surface of said base member, said reservoir for receiving grease drippings directed downwardly and away from said drip pan; and

a plurality of access doors pivotally connected to said side panels respectively and extending along a partial length thereof and substantially parallel to the axis, said plurality of access doors being disposed adjacent said plurality of baskets and being movable between open and closed positions so that a user can effectively access the cavity.

19. The barbeque grill of claim 18, wherein said top member further comprises: a lid pivotally connected thereto and for selectively covering said grill surface during cooking operations.

20. The barbeque grill of claim 18, wherein said drip pan is disposed substantially medially of said plurality of baskets and is engaged therewith respectively.